

a speech input system configured to receive a spoken command and to convert the spoken command into corresponding control signals, the control system including:

an operating element configured for manual actuation by an operating person to activate the system; and

A2  
a display device configured to indicate to the operating person, upon the activation of the speech input system, the readiness condition of the system to receive voice commands, the display device including an arrangement configured to mechanically deflect one of the element and a part thereof, the deflection arrangement operatively connected to the speech input system, the deflection arrangement configured to be driven by the speech input system and to communicate the readiness condition to an operating hand of the operating person in a direct, tactile manner when the readiness of the system occurs.--.

---

#### **REMARKS**

This Preliminary Amendment cancels, without prejudice, claims 1 to 16 in the underlying PCT Application No. PCT/DE01/01772. This Preliminary Amendment adds new claims 17 to 36. The new claims, inter alia, conform the claims to U.S. Patent and Trademark Office rules and does not add any new matter to the application.

In accordance with 37 C.F.R. § 1.121(b)(3), the Substitute Specification (including the Abstract, but without the claims) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to U.S. Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. §§ 1.121(b)(3)(iii) and 1.125(b)(2), a Marked Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) is respectfully requested.

The underlying PCT Application No. PCT/DE01/01772 includes an International Search Report, dated September 20, 2001, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.



It is respectfully submitted that the subject matter of the present application is new, non-obvious and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully submitted,

KENYON & KENYON

Dated: MARCH 29, 2002

By:

Richard L. Mayer by Alfred W. Kenyon  
Richard L. Mayer  
Reg. No. 22,490

One Broadway  
New York, New York 10004  
(212) 425-7200

Reg. No.  
42,191

CUSTOMER NO. 26646



26646

PATENT TRADEMARK OFFICE

[10191/2121]

METHOD AND SYSTEM FOR ACOUSTICAL FUNCTION  
CONTROL IN A MOTOR VEHICLE

[Background Information]

] FIELD OF THE INVENTION

The present invention relates to a method and a control system for acoustical function control in a motor vehicle using a speech input system that receives spoken commands and converts them into corresponding control signals, the system being activated by an operational element that is manually activated and, upon being activated, outputting to an operating person the indication of readiness to receive a spoken command.

BACKGROUND INFORMATION

Currently, speech input systems must be activated by the user shortly before the inputting of a relevant voice command. A so-called "Push-To-Talk" activation of this type is usually [carried out] performed by a push-button on the steering wheel rim. The system must signal back to the user when it is ready to respond to his command, i.e., provide a readiness indication. It is [known] conventional to realize this indication of readiness using a color change of an optical symbol on a display or using a short, one-time tone. Because in actual urban driving, the use of voice inputting is usually a secondary task, after the safe driving of the vehicle, and the driver is often subject to significant mental stress by the actual task of driving, he [can] may overlook the optical symbol indicator on the display, it is possible for him not to hear the acoustical check-back signal, or he [can] may forget that the check-back signal has already [taken place] occurred. As a result, he is uncertain with regard to the condition of the system, which can lead to operating errors, faulty functioning, and consequently to a lack of acceptance by the

user of a function control system that operates on the basis of voice input in a motor vehicle.

[Objective and Advantages of the Invention

5 ] SUMMARY

[It is the] It is an objective of the present invention to [make possible] provide a method [according to the species] and a control system [according to the species,] such that voice-input function control in the motor vehicle is  
10 simplified and its functional reliability increased. At the same time, [the] a goal is to achieve clarity in a simple manner concerning the condition of the system without requiring a glance and without annoying the passengers, and to increase the acceptance of speech input systems of this type  
15 for function control in a motor vehicle.

It is also an objective of the present invention to [indicate] provide a combined operating/indicator element that is suitable for the control system according to the present  
20 invention.

As a result of the fact that the indication of the readiness condition is effected by a mechanical deflection from a preestablished position of the combined operating/indicator  
25 element, or a part thereof, in an immediate response to the tactile sensation of the operating hand of the operating person, the driver is constantly informed concerning the condition: *Ready* or *Not Ready* of a speech input system, without having to cast his glance at a particular display. In  
30 addition, in this manner, the correct time for a voice command [is] may be clearly signaled to the driver so that the recognition rate of the voice recognition in the speech input system is improved.

35 After a valid voice command is recognized, the control system for its part [can] may indicate that it is 'at present no

longer ready to input a further command. For this purpose, the combined operating/indicator element, or the part thereof, [can] may once again be set in its original condition.

5 The readiness indication as a result of the mechanical deflection of the operating/indicator element, or a part thereof, [can] may be effected statically, in that the operating/indicator element, or part thereof, experiences a static change in shape or position during the readiness  
10 condition of the control system.

In [the exemplary] an example embodiment, if the operating/indicator element is embodied by a switch or key on the steering wheel rim, it is possible, for indicating  
15 readiness, to recess the push-button or the sliding head of the key or switch, which was pressed by the driver to activate system, so far into the housing that the finger of the operating hand senses a depression or opening in the housing. This static change in shape of the operating/indicator element  
20 suggests to the user that the system is "opened" like a door. This analogy [can] may be taken even further if the operating/indicator element is given the shape, e.g., of a raised ear, and the readiness to hear, i.e., to receive a spoken command, is signaled by a lowering of the ear. This, in  
25 turn, is brought about by the control system.

An alternative possibility is not to change the shape or position of the operating/indicator element, or a part thereof, statically during readiness, but to set the  
30 operating/indicator element, or a part thereof, in vibration to indicate readiness. In the meaning of the present invention, a vibration [is] may also [to] be understood as a deflection of the operating/indicator element or a part thereof.

According to [the currently preferred] one example embodiment,  
the combined operating/indicator element is a key or switch  
that [can] may be installed on the steering wheel of a motor  
vehicle, [whose] the movable part of which, i.e., [whose] the  
5 key or switch sliding head, is placed in vibration or is moved  
in order to indicate the readiness condition using an  
electromotor, electromagnetic, or piezoelectrical actuator  
organ located in the interior of the operating/indicator  
element. In place of this, it is also possible to use other  
10 [known] conventional actuators.

Below, on the basis of the drawing, [a currently preferred  
exemplary] an example embodiment of the method according to  
the present invention and of the control system are described,  
15 as well as a combined operating/indicator element [designed]  
configured for the control system.

[Drawing

] BRIEF DESCRIPTION OF THE DRAWINGS

20 Figure 1 schematically [depicts] illustrates a basic system  
structure of a control system for acoustical function control  
in accordance with the present invention[, and].

Figures 2 A-C [depict] are function-time diagrams, which  
25 illustrate the basic time curve of the functions of the  
control system [depicted] illustrated in Figure 1.

[Exemplary Embodiment

] DETAILED DESCRIPTION

30 Figure 1 [depicts] illustrates schematically and in the form  
of function blocks a control system for acoustical function  
control in a motor vehicle, generally designated as reference  
numeral 1. Via a microphone 16, a speech input system that is  
made up of a voice recognition block 10 and a control block  
35 11, control system 1 in the activated condition [can] may

receive spoken commands from an operating person and [can] may convert them into control signals for controlling various functions in the motor vehicle as well as, if appropriate, also around the motor vehicle.

5

Before the input of a relevant voice command by the user, the system is activated by the pressure of the finger of his hand on a key or switch sliding head 13 of a key or switch 12 secured on steering wheel rim 15, the key pressure or switching operation being conveyed to control block 11 of system 1 as an activating signal.

10

Control block 11, [depicted] illustrated in Figure 1, functions to control voice recognition block 10, to activate microphone 16, to input the switching condition of operating element 12, and to actuate the sliding head for the readiness indication, or for triggering the vibration.

15

System 1, or control block 11 of the speech input system, signals back to the user when it is ready to respond to his voice command, i.e., it delivers a readiness indication. For this readiness indication, after combined operating/indicator element 12 has been actuated by the user, e.g., through finger pressure, to activate the system, the element is brought by control block 11 of system 1 into a condition which [can] may be detected by the same finger, or by other parts of the hand of the user in a direct tactile manner. For this purpose, in the [exemplary] example embodiment, sliding head 17 of key 13, extending into the interior of operating/indicator element 12, which was pressed by the driver for the purpose of activation, is retracted, e.g., by an electromagnet 14 upon a signal from control block 11, so far into the housing of operating element 12 that the finger senses a depression or opening in the housing. A signaling of this type for the readiness condition clearly suggests to the user that the system is "opened" like a door.

20

25

30

35

As [was mentioned,] indicated above, this analogy [can] may be taken even further, by giving to the combined operating/indicator element the shape of an ear and by signaling the readiness of the system to respond, i.e., to accept voice commands, by a lowering of the ear.

In place of using an electromagnet or electromotor 14 in the interior of operating/indicator element 12, for retracting and holding sliding head 17 of key 13 in the interior of the housing, it [is] may also be possible to use piezo actuators and other similar [known] conventional actuators.

An alternative configuration[, which is not specifically depicted in Figure 1, can] may set key 13 in vibration in order to indicate readiness. In this case as well, the operating/indicator element, during the readiness of system 1, experiences a mechanical deflection, which is detectable as vibration in a directly tactile manner.

The function-time diagrams [depicted] illustrated in Figures 2A-2C indicate in principle the time curve of functions of the version of control system 1 [depicted] illustrated in Figure 1, [whose] the operating/indicator element of which is furnished with projecting/retracting key 13 and sliding head 17.

Part A of Figure 2 [depicts] illustrates the activation of key 13 of operating/indicator element 12 by the finger of the user, the closing of the contact of the key, the inputting into control block 11, and the activating of voice recognition block 10. In central part B, Figure 2 [shows] illustrates that, after the activation, the system signals its voice input readiness by retracting sliding head 17 and with it key 13 into the housing of operating/indicator element 12. Double arrow T thus indicates duration T of the readiness condition of the system. During readiness condition T, the user [can]



may input a voice command into system 1 via microphone 16 in accordance with lower part C of Figure 2. Voice recognition block 10 recognizes the spoken command and converts it into corresponding control signals for various control tasks inside the motor vehicle[, not specified in any greater detail,] or optionally outside the motor vehicle (e.g., opening a garage door).

After the voice command of the user input into microphone 16 has been recognized by voice recognition block 10 and has been converted into the corresponding control signals, system 1 once again indicates via control block 11 and operating/indicator element 12 that it is at present no longer ready for the inputting of a further command. For this purpose, in accordance with central part B of Figure 2, operating/indicator element 12, or its key 13, is once again set in its original condition. In the [depicted exemplary] illustrated example embodiment, the head of key 13 once again extends out of the housing of the operating/indicator element. In [the] an alternative example embodiment, the vibration of the key then ceases.

In the example method according to the present invention for acoustical function control in a motor vehicle, [depicted] illustrated above by way of example, as well as in the control system [designed] configured for this purpose, the driver [is] may be constantly informed concerning the condition of the speech input system, without having to specially direct his glance to a display. The driver [can] may therefore direct his eyes and attention to the events on the road, parallel to inputting a spoken command. The driver senses through his hand in a direct, tactile manner the correct time for a voice command, as a result of which the recognition rate of the speech input system is not impaired.

The driver [can] may always form a correct picture of the condition of the speech input system, so that he feels more secure in the dialogue with the speech input system and is no longer hampered in his driving performance by irritation.

5 Passengers are not affected by this form of providing information.

[Abstract

] **ABSTRACT**

[The present invention relates to] **In** a method and a control  
system for acoustical function control in a motor vehicle  
5 using a speech input system [(10, 11)] that receives a spoken  
command and converts it into corresponding control signals,  
the system [being] **is** activated by an operating element [(12)]  
that is actuated manually and, upon being actuated,  
[outputting] **outputs** to an operating person an indication of  
10 its readiness to receive a voice command. **The** [,  
wherein the] indication is effected by a mechanical deflection  
from a preestablished position of the operating element[(12)],  
or a part [(13)] thereof, so as to directly influence the  
tactile sense of the operating hand of the operating  
15 person[(Figure 1)].